


iCHAIR MC BASIC

1.609

 **Allowed user weight**
120 kg (incl. additional load)





Long-life LED lighting



VR2 controls



Netti UNO Back (optional)



Hinged backrest

Simple reliable

EFFICIENCY

- Effectiveness through simple maintenance and a high level of service friendliness
- Modular structure of the iChair-family enables compatibility of parts and parts groups
- Numerous adjustment possibilities enable individual adaptation
- High-grade engines
- Long-life LED lighting

THERAPEUTIC BENEFIT

- Ideal for retaining mobility at home, at the desk or in the office

FIELD OF USE

- For permanent and all-day use for independent mobility, also with extreme functional limitations
- For working and active people, who need one wheelchair for different everyday situations
- Indoor spaces can easily be mastered due to the compact dimensions and high level of agility
- For indoor and outdoor use

ORDER

COST ESTIMATE

CUSTOM DESIGN

Please fax the completed order form to: **05733 922 9311**

Customer service: **05733 922 311**

Billing address / Customer ref. no.:

Delivery address:

Consignment / Comments:

Order quantity:

MEYRA



Allowed user weight

120 kg (incl. additional load)



Hints

Our Terms and Conditions as stated at www.meyra.de/AGB shall apply
You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01/01/2021 - 12/31/2021.
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check



Technical specifications

¹⁾ see category seat width

³⁾ without legrests and without armrests

²⁾ measured with seat tilt 4° (without seat cushion)

Seat widths in mm	430 - 550 ¹⁾
Seat depth in mm	400 - 530
Back support height in mm	500 ²⁾
Lower shank length in mm	280 - 430 ²⁾
Arm support height in mm	240 - 350 ²⁾
Front seat height in mm	440 - 510 ²⁾
Length with footrest in mm	1110
Ready for use width in mm	590
Height without head support in mm	1010
Transport length in mm	840
Transport height min. in mm	600
Castor wheels diameter	225 x 70 (9")
Drive wheels diameter	320 x 60 (12,5 x 2,5")
Max. obstacle height in mm	60
Turning radius in mm	840
User weight	120 kg
Empty weight	81 kg ³⁾
Permissible overall weight	220 kg
Max. additional loading	10 kg
Driving speed	6 km/h
Motor power	2 x 180 W
RANGE	25 km
Permitted inclination/slopes	15%
Back support angle mechanical	-10° - 30°
Seat camber mechanical	0° - 10°
Form of steering	indirect


Please select by ticking the relevant boxes

*SBI - Sonderbau/Individuallösung

Standard version: If no other selection is made, the standard version will be delivered.

Basic configuration

CODE	DESCRIPTION	EQUIPMENT
<input type="checkbox"/> 5159	MC BASIC	Maintenance-free batteries, 50 AH (20H), Standard rim
<input type="checkbox"/> 5159	MC BASIC Plus	Maintenance-free batteries, 50 Ah(20h), two-part rim Drive wheel strap

 Version AOK Baden Württemberg

Chassis/Motor performance

CODE	SPEED	MOTOR POWER	SUSPENSION	RANGE
<input type="checkbox"/> 892/115	6 km/h	2 x 180 Watt-Motor	up to 120 kg	28 km

Seat width (SW)

CODE	DESCRIPTION
<input type="checkbox"/> 43	430 mm seat depth, continuously adjustable through the arm supports from 430 - 550 mm, seat surface width 430 mm

Seat depth

CODE	DESCRIPTION
<input type="checkbox"/> 619	460 mm

Steering wheel/front seat height (FSH)

CODE	FSH (mm)	DESCRIPTION
<input type="checkbox"/> 146/163	480	9"- Standard-air tyre

Drive wheels/Suspension

CODE	DESCRIPTION
<input type="checkbox"/> 909/815/846	2"-puncture protected pneumatic tyres, suspension up to 120 kg

Please select by ticking the relevant boxes

*SBI - Sonderbau/Individuallösung

Standard version: If no other selection is made, the standard version will be delivered.

Seat tilting/seat lift

CODE	DESCRIPTION	Seat angle
<input type="checkbox"/> 119	Mechanic seat tilt, in steps	0° to 10°

Seat system/Seat unit

CODE	DESCRIPTION
<input type="checkbox"/> 561/738	Seat belt with 60 mm seat cushion, textile black

Back systems

CODE	DESCRIPTION
<input type="checkbox"/> 738/737	Standard back support strap with continuous push bar

Back support options/Adjustments

CODE	DESCRIPTION
<input type="checkbox"/> 401	mechanical back angle adjustment -10° to +30° adjustable, in 10° -steps

Arm supports and arm pads

CODE	DESCRIPTION	WIDTH ADJUSTMENT
<input type="checkbox"/> 106	Standard arm support with padded arm support	SW +120 mm

Leg supports

CODE	DESCRIPTION
<input type="checkbox"/> 93	Legrests, detachable and swing-away

Footrests

CODE	DESCRIPTION
<input type="checkbox"/> 798	Divided footrest, hight adjustable, flip up and angle adjustable

Please select by ticking the relevant boxes *SBI - Sonderbau/Individuallösung Standard version: If no other selection is made, the standard version will be delivered.

Battery charger

CODE	DESCRIPTION
------	-------------

<input type="checkbox"/> 731	Charger 6 A
------------------------------	-------------

Lighting

CODE	DESCRIPTION
------	-------------

<input type="checkbox"/> 932	Active lighting front and rear, acc. to StVZO
------------------------------	---

Operating modules/Options

CODE	DESCRIPTION
------	-------------

<input type="checkbox"/> 74/408	Operating module VR2, mounted right - only for 6 km/h (refittable to left)
---------------------------------	--

Operating module bracket

CODE	DESCRIPTION
------	-------------

<input type="checkbox"/> 4860	Operating module holder length and height adjustable and swiveling
-------------------------------	--

Frame colour

CODE	DESCRIPTION
------	-------------

<input type="checkbox"/> 207	Matt black
------------------------------	------------

Remarks

Date

City

Signature